

H125 Signage Player

The H125 is a mid-range triple display signage and media player built for reliable 24/7 use. It is compact, fanless, and supports Windows 10 or 11 IoT or standard Windows 11 Pro.



Windows 10/11
IoT



Rated for 24/7
Use



Fanless



RTC Power
Scheduling



Triple 4K 60 Hz

Ports



1. Power Button
2. USB 3.2 Gen 2 (Type-A)
3. USB 3.2 Gen 2 (Type-C)
4. 3.5mm Audio (1 x Mic & 1 x Headphones)

5. DB9 RS232



5. DB9 RS232
6. DC-in
7. LAN (RJ45)
8. HDMI 2.0
9. DisplayPort 1.4
10. HDMI 2.0



Intel Twin Lake

Performance

Processor	Intel N150 - 4C/4T
Memory	Up to 16GB DDR4 @ 3200MHz
Storage	Up to 4TB M.2 NVMe SSD
Graphics	Intel Graphics
Operating System	Windows 11 - Home / Pro / Enterprise IoT No operating system - Optional

System

Power Supply	External 36W brick (12V 3A, 5.5mm x 2.5mm)
RTC	Power scheduling supported
TPM	TPM 2.0

Physical

In the box	H125 system Power supply VESA mounting bracket
Dimensions	151mm x 128mm x 26mm
Weight	Gross Weight: 1.46Kg Net Weight: 0.71Kg
Packaging	Paper: 229g (82.67%) Plastic: 48g (17.33%)

Optional Extras

Upgrades	Intel Wi-Fi 6E (802.11ax) + BT 5.3
----------	------------------------------------

Conformity

Conformity	CE / ROHS
------------	-----------

Connectivity

Networking	Realtek 1Gb LAN Wi-Fi 6 & Bluetooth 5.2
Front IO	1 x USB 3.2 Gen 2 (Type-C) 2 x USB 3.2 Gen 2 (Type-A) 2 x 3.5mm Audio (1 x Mic & 1 x Headphones)
Side IO	1 x DB9 RS232
Rear IO	2 x HDMI 2.0 1 x DisplayPort 1.4 2 x USB 2.0 (Type-A) 1 x LAN (RJ45) 1 x DC-in

Warranty

Standard	1 year collect and return
Optional Upgrades	Up to 5 years total cover Extended Service Plan

Environment

Operating Temperature	-5°C to 45°C
Operating Humidity	10% to 90% non-condensing
Storage Temperature	-20°C to 70°C
Storage Humidity	5% to 95% non-condensing

Please note that the system images are examples and may differ based on chosen specifications. Some products shown in system images may be subject to availability. Please contact our team if you have any questions regarding configuration.

Supported Resolutions

Supported Resolutions

Video Format			Output	
Shorthand	Resolution	Refresh rate (Hz)	HDMI	Displayport
1080p	1920×1080	30	Yes	Yes
		60	Yes	Yes
4K	3840×2160	30	Yes	Yes
		60	Yes	Yes
5K	5120×2880	30	No	No
		60	No	No
8K	7680×4320	30	No	No
		60	No	No